## Contactor, 24 V DC, 3 pole, 380 V 400 V, 3 kW, Contacts N/O = Normally open= 1 N/O, Screw terminals, DC operation



Part no. DILEEM-10-G-EA(24VDC) 189980

roduct name	Eaton Moeller® series DILEEM Mini contactor
'art no.	DILEEM-10-G-EA(24VDC)
EAN	4015081879762
Product Length/Depth	52 millimetre
Product height	58 millimetre
Product width	45 millimetre
Product weight Product weight	0.17 kilogram
Compliances	CE CE Marked RoHS conform
Product Tradename	DILEEM
Product Type	Mini contactor
Product Sub Type	None
Voltage type	DC
Rated operational power at AC-3, 380/400 V, 50 Hz	3 kW
Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V	22 A
Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V	6.6 A
Rated control supply voltage (Us) at AC, 50 Hz - min	0 V
Rated control supply voltage (Us) at AC, 50 Hz - max	0 V
Rated control supply voltage (Us) at AC, 60 Hz - min	0 V
Rated control supply voltage (Us) at AC, 60 Hz - max	0 V
Rated control supply voltage (Us) at DC - min	24 V
Rated control supply voltage (Us) at DC - max	24 V
Number of auxiliary contacts (normally closed contacts)	0
Number of auxiliary contacts (normally open contacts)	1

## **Technical data ETIM 8.0**

C000066)	
h technology / Contactor	(LV) / Power contactor, AC switching (ecl@ss10.0.1-27-37-10-03 [AAB718015])
V	0 - 0
V	0 - 0
V	24 - 24
	DC
Α	22
Α	6.6
kW	3
Α	5
kW	2.2
kW	2.2
	No
	1
	0
	Screw connection
	0
	h technology / Contactor  V  V  V  A  A  kW  A

3