

Contactors, 3 pole, 380 V 400 V 30 kW, RDC 24: 24 - 27 V DC, DC operation, Screw terminals



**Part no. DILM65-EA(RDC24)
190014**

Product name	Eaton Moeller® series DILM contactor
Part no.	DILM65-EA(RDC24)
EAN	4015081880102
Product Length/Depth	132.1 millimetre
Product height	115 millimetre
Product width	55 millimetre
Product weight	1.052 kilogram
Compliances	RoHS conform CE Marked CE
Product Tradename	DILM
Product Type	Contactors
Product Sub Type	None
Voltage type	DC
Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V	98 A
Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V	65 A
Rated operational power at AC-3, 380/400 V, 50 Hz	30 kW
Rated control supply voltage (Us) at AC, 50 Hz - min	0 V
Rated control supply voltage (Us) at AC, 50 Hz - max	0 V
Rated control supply voltage (Us) at AC, 60 Hz - min	0 V
Rated control supply voltage (Us) at AC, 60 Hz - max	0 V
Rated control supply voltage (Us) at DC - min	24 V
Rated control supply voltage (Us) at DC - max	27 V
Number of auxiliary contacts (normally closed contacts)	0
Number of auxiliary contacts (normally open contacts)	0

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactors (LV) / Power contactor, AC switching (ecl@ss10.0.1-27-37-10-03 [AAB718015])			
Rated control supply voltage Us at AC 50HZ	V		0 - 0
Rated control supply voltage Us at AC 60HZ	V		0 - 0
Rated control supply voltage Us at DC	V		24 - 27
Voltage type for actuating			DC
Rated operation current Ie at AC-1, 400 V	A		98
Rated operation current Ie at AC-3, 400 V	A		65
Rated operation power at AC-3, 400 V	kW		30
Rated operation current Ie at AC-4, 400 V	A		25
Rated operation power at AC-4, 400 V	kW		12
Rated operation power NEMA	kW		37
Modular version			No
Number of auxiliary contacts as normally open contact			0
Number of auxiliary contacts as normally closed contact			0
Type of electrical connection of main circuit			Screw connection
Number of normally closed contacts as main contact			0

